



NOTES:

- 1) ENCLOSURE IS A NEMA-1 TYPE CABINET WITHOUT GASKETS.
- 2) ALLOW 6in (152mm) OF FREE AIR (TOP AND FRONT OF CABINET) FOR VENTILATION.
- 3) FOUR (4) KEY-HOLE SLOTS ARE PROVIDED ON THE BACK OF ENCLOSURE AS SHOWN, FOR WALL-MOUNTING WITH .25in (6.25mm) HARDWARE.
- 4) FOUR (4) 1.31in/33mm DIA KNOCKOUTS ARE PROVIDED AS SHOWN, WITH TWO (2) ADDITIONAL KNOCKOUTS FEATURED ON BOTTOM PANEL OF ENCLOSURE. USE OF ANY OF THESE FOUR (4) LOWER CONDUIT KNOCKOUTS WILL ALLOW REMOVAL OF THE CABINET SHROUD WITHOUT REMOVAL OF EXTERNAL WIRING.
- 5) BATTERY CHARGER SHIPPING WEIGHT RANGE: APPROXIMATELY 44-20 lbs. / 80-36 kg.
- 6) STANARD CIRCUIT BREAKER LOCATION AT BOTTOM OF ENCLOSURE. 480VAC AND/OR MEDIUM/HIGH AIC CIRCUIT BREAKERS RELOCATED TO TOP PENTHOUSE ENCLOSURE.

DUAL DIMENSIONS in mm

				THIRD ANGLE PROJECTION		TITLE AT10.1 SERIES BATTERY CHARGER OUTLINE: NEMA-1 STYLE-586 ENCLOSURE W/PENTHOUSE	
				DRAWN BY MCR 022603		DRAWING No JE5023-01	
				APPROVED		REV 0 B	
				UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:		SCALE NTS	
0	E1151	022603				PART No JE5023-01	SHEET 1 OF 1
REV	ECN No	DATE	APP				