

AT30 SERIES BATTERY CHARGER ORDERING WORKSHEET

JF5021-03

Customer Information

Customer Purchase Order		Battery Type	
Quote Number		# of Cells	
Contact Name		Float Voltage Setting	Vdc
Contact Phone Number		Equalize Voltage Setting	Vdc

AT30 Battery Charger Factory Ordering Code (standard specifications) All Ratings (25-1,000 Adc Output)

AT30																
A	B	C	D	E	F	G	H	J	K	L	M	N	P			

	DESCRIPTION	CODE	FEATURE		
A	SERIES	AT30	AT30 CHARGER		
B	NOMINAL DC OUTPUT VOLTAGE	012	12 Vdc		
		024	24 Vdc		
		048	48 Vdc		
		130	130 Vdc		
C	NOMINAL DC OUTPUT CURRENT	CODE	FEATURE	CODE	FEATURE
		025	25 Adc	200	200 Adc
		030	30 Adc	250	250 Adc
		040	40 Adc	300	300 Adc
		050	50 Adc	400	400 Adc
		075	75 Adc	500	500 Adc
		100	100 Adc	600	600 Adc
		125	125 Adc	800	800 Adc
		150	150 Adc	1K0	1,000 Adc
		D	FILTERING	U	UNFILTERED
F	FILTERED				
E	ELIMINATOR				
E	AC INPUT VOLTAGE	208	208 Vac 60 Hz		
		240	240 Vac 60 Hz		
		480	480 Vac 60 Hz		
		220	220 Vac 50/60 Hz		
		380	380 Vac 50/60 Hz		
416	416 Vac 50/60 Hz				

	DESCRIPTION	CODE	FEATURE
F	AC CIRCUIT BREAKER RATING (SEE TABLE)	S	STANDARD
		M	MEDIUM AIC
		H	HIGH AIC
		0	NO AC BREAKER
G	AC FUSES (200 KAIC)	F	SUPPLIED
		X	NOT SUPPLIED
H	DC CIRCUIT BREAKER RATING (SEE TABLE)	S	STANDARD
		M	MEDIUM AIC
		H	HIGH AIC
		0	NO DC BREAKER
J	DC FUSES (20 KAIC)	F	SUPPLIED
		X	NOT SUPPLIED
K	AUXILIARY ALARM RELAY BOARD	A	SUPPLIED
		X	NOT SUPPLIED
L	GROUND PAD	G	SUPPLIED
		X	NOT SUPPLIED
M	LIGHTNING ARRESTOR	L	SUPPLIED
		X	NOT SUPPLIED
N	TREATMENTS	F	FUNGUS PROOFING
		S	STATIC PROOFING
		X	NOT INCLUDED
P	DRIP SHIELDS	D	INSTALLED
		X	NOT SUPPLIED

DESCRIPTION CODE FEATURE

DESCRIPTION CODE FEATURE

AT30 Options - All Ratings (25-1000 Adc Output)

<input type="checkbox"/>	EI0193-03	23in rack mtg bkts (S-5018)	<input type="checkbox"/>	EI5037-0X	Style-5018 NEMA-4/12/13 type enclosure
<input type="checkbox"/>	EI5008-00	Wall-mount brackets (S-5018)	<input type="checkbox"/>	consult factory	Style-5030 or Style-5031 NEMA-4/12/13 type enclosure
<input type="checkbox"/>	EJ5041-0X	Cabinet heater assembly	<input type="checkbox"/>	EJ5033-0X	External temperature compensation probe <input type="text"/> length
<input type="checkbox"/>	EI5038-0X	Padlock for front panel	<input type="checkbox"/>	EJ5037-0X	DNP3 Level 2 / Modbus communications module
<input type="checkbox"/>	EJ5088-0X	Ground detect dc vmeter w/sw	<input type="checkbox"/>	PM5005-00	Compatible modem option for communications module
<input type="checkbox"/>	consult factory	AC metering (analog or digital)	<input type="checkbox"/>	EH5026-0X	Modem cable <input type="text"/> length

Additional Features / Customer Notes

Input / Output Circuit Breaker Ampere Interrupting Ratings Table

CODE	TYPE	AC RATINGS (ALL INPUT VOLTAGES)	DC RATINGS (125 Vdc)	DC RATINGS (250 Vdc)
S	STANDARD AIC	5,000 AIC	5,000 AIC	-
M	MEDIUM AIC	25,000 AIC	10,000 AIC	10,000 AIC
H	HIGH AIC	65,000 AIC	25,000 AIC	25,000 AIC